



XN32TF-P3 PHOTOVOLTAIC MODULES

XN32SERIES HALF-CUT PV MODULES


PEAK POWER: 255-265 Wp

FEATURES INCLUDE:

- 64 half-cut N-Topcon cells comprised by double layers of glasses.
- Positive power tolerance of 0~+3% improves system performance.
- Industry-leading module efficiency: maximum efficiency of 12.26%.
- Tested up to 5400Pa for maximum load resistance.
- Verified resistance against PID effects.
- Progressive Power Warranty guarantees 87.4% of rated power at 30 years.
- Manufactured globally with world-class quality standards


QUALITY, RELIABILITY, AND KWH YIELD

MOTECH modules are powered by industry acknowledged high performance, reliable silicon cells. 25 years of experience in solar module engineering and design, along with rigorous durability and performance tests, ensure reliable lifetime performance and maximum kWh yield.



30-YEAR PROGRESSIVE WARRANTY*

- 30-year progressive power warranty
- 12-year warranty on materials and workmanship




CERTIFICATIONS & STANDARDS*





XN32TF-P3 PHOTOVOLTAIC MODULES


PHYSICAL CHARACTERISTICS



PHYSICAL DESIGN PROPERTIES

Dimension	1906×1134×30mm
Weight	27.1kg±5%
Front Glass	2.0 mm Semi-tempered Coated PV Glass
Back Glass	2.0 mm Glazed Glass
Junction Box	Protection class IP68
Output Cables	Φ4.0mm ² , 500mm/500mm, or customized length
Connectors	MC4 Compatible
Light transmittance	51.1%
Packing	36 pcs/pallet, 864 pcs/container(40'HQ)

IV CURVE



ELECTRICAL PERFORMANCE

XN32TF-P3-255

XN32TF-P3-260

XN32TF-P3-265

Electrical Performance @ STC (Power Measurement Uncertainty±3%)			
Maximum Power Pmax[Wp]	255	260	265
Max. Power Voltage Vmpp(V)	19.94	20.18	20.42
Max. Power Current Impp(A)	12.79	12.89	12.98
Open Circuit Voltage Voc(V)	23.06	23.32	23.55
Short Circuit Current Isc(A)	13.47	13.56	13.65
Module Efficiency (%)	11.80%	12.03%	12.26%

Power Gain (Electrical Performance @ STC) (Power Measurement Uncertainty±3%)			
5%	Pmax[Wp]	267	273
	Module Efficiency (%)	12.35%	12.63%
15%	Pmax[Wp]	293	299
	Module Efficiency (%)	13.56%	13.83%
25%	Pmax[Wp]	318	325
	Module Efficiency (%)	14.71%	15.04%

ELECTRICAL PERFORMANCE PARAMETERS

Isc Temperature Coefficient	α (%/°C)	+0.045	Maximum Series Fuse Rating	30A
Voc Temperature Coefficient	β (%/°C)	-0.25	Max. System Voltage (IEC)	1500V
Pmax Temperature Coefficient	γ (%/°C)	-0.29	Nominal Operating CellTemp.(NOCT)	45°C ± 2°C

IV parameters are rated at Standard Test Conditions (Irradiance of 1000 W/m², AM 1.5, cell temperature 25°C). All measurements are guaranteed at the laminate leads. NOCT is measured at 800 W/m², 20°C ambient, and 1 m/s windspeed. Specifications are subject to change without notice.

Motech reserves the rights of final interpretation and revision on this datasheet.

M31-2404-012-A



Motech Industries, Inc. Solar Division
Tainan Science Park I No.2, Dashun 9th Rd., Xinshi Dist., Tainan City, 74145, Taiwan
Tel: +886-6-5050789 Fax: +886-6-5051789
E-mail: modules@motech.com.tw

www.motechsolar.com